



Pipe Lifting Clamp TPH

Product information

General: Horizontal pipe lifting clamp TPH/TPH-HD - Non marking. Clamp for horizontal lifting and transporting of steel and concrete pipes without damaging the product.

Model THP: Standard clamp

Model THP-HD: special for extreme heavy duty lifting situations

Features:

- TPH Jaw is covered with a special high quality pressure resistant plastic.
- TPH-HD Jaw is covered with special high quality extreme high pressure resistant plastic.
- Maintenance-friendly clamps, plastic pressure resistant cover is easy to change.
- TPH-HD has special handle for easy handling.
- Compact design and high lifting capacity.
- Lightweight design for easy handling.
- Tough quality heavy duty body.

Marking: According to standard, Type, serial number, WLL, Jaw opening and CE marking.

Temperature range: TPH: - 40°C to + 50°C. / TPH-HD - 30°C to + 80°C.

Standard: EN 13155

Part code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	U mm	T mm	X mm	Y mm	Weight kg	Delivery time
44010071B	1.5 TPH	1.5	40	120	70	50	185	16	41	25	2	12
44010077B	3 TPH	3	40	120	70	50	185	16	41	25	2	12
44010078B	4 TPH	4	50	140	70	58	204	26	41	25	3	12
44010196B	5 TPH-HD	5	60	309	100	85	232	26	80	20	6.7	12
44010079B	6 TPH	6	50	140	70	58	204	26	41	25	3	12
44010191B	8 TPH	8	70	140	70	58	224	26	45	25	3.4	12
44010188B	10TPH	10	70	140	70	58	224	26	85	45	5	12
44010192B	10 TPH-HD	10	60	319	100	85	236	36	80	30	9.7	12
44010030B	12TPH	12	70	140	70	58	224	26	85	45	7	12
44010189B	15TPH	15	70	155	70	76	250	26	100	60	9	12
44010190B	20TPH	20	70	155	70	76	250	26	100	60	9	12
44010193B	20 TPH-HD	20	60	362	100	105	285	51	80	35	14	12
44010194B	30 TPH-HD	30	60	387	100	115	310	58	80	40	19	12
44010195B	60 TPH-HD	60	60	418	100	115	350	85	80	60	28.5	12

Blueprint

