



## Vertical Lifting Clamp TS/TSE/STS

### Product information

For vertical lifting and transporting of steel plates. The TS lifting clamps are equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered. The clamp is locked in closed as well as in open position. The STS is similar but offers a larger jaw opening.

#### Features:

- Lightweight design for easy handling.
- Tough quality heavy duty welded shell body.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- Clamp is locked in closed as well as open position.
- Maintenance-friendly, easy to exchange parts which are available upon request .
- Signal colouring on lifting eye and locking lever for extra safety.

**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

**Temperature range:** - 40°C up to +100°C.

**Standard:** EN 13155

**Note:** Hardness level of the material surface may not exceed 37 HRC (345 HB, 1166 N/mm<sup>2</sup>).

**Warning:** Min. load is 10% of max. WLL.

Part Code	Code	WLL ton	Jaw width mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Weight kg	Delivery time
44010085B	0.75 TS	0.75	0-13	47	30	202	100	37	37	10	1.7	12
44010015B	1 TSE	1	0-25	56	45	263	141	37	47	15	3.5	12
44010016B	2 TSE*	2	0-35	78	64	336	183	56	56	16	7	12
44010215B	3 TSE*	3	0-35	78	64	336	183	56	56	16	7	12

44010198B	4.5 TS	4.5	0-25	85	70	423	203	60	77	20	15	12
44010091B	4.5 TSE	4.5	0-45	85	70	425	228	60	78	20	16	12
44010014B	6 TS	6	0-32	114	75	490	225	78	78	20	19	12
44010017B	6 TSE	6	0-50	114	75	490	259	82	78	20	21	12
44010147B	6 STS	6	40-90	114	75	486	275	70	78	20	21	12
44010111B	7.5 TS	7.5	0-40	111	75	530	246	76	82	20	24	12
44010087B	7.5 TSE	7.5	0-55	111	75	522	267	70	86	20	26	12
44010140B	7.5 STS	7.5	50-100	111	75	524	312	70	86	20	26.5	12
44010082B	9 TS	9	0-55	111	75	522	267	70	86	20	27	12
44010146B	9 STS	9	50-100	111	75	522	312	70	86	20	27.5	12
44010088B	12 TS	12	0-52	148	85	617	295	100	94	44	37	12
44010141B	12 STS	12	50-100	152	85	615	344	100	94	44	41	12
44010013B	15 TS	15	0-76	209	86	810	373	136	106	49	70	12
44010142B	15 STS	15	80-150	224	86	800	450	136	106	49	76	12
44010200B	17 TS	17	0-76	209	86	810	373	136	106	49	71	12
44010201B	20 TS	20	0-80	250	100	933	563	153	140	66	149	12
44010143B	20 STS	20	80-150	249	100	924	640	153	140	66	160	12
44010086B	25 TS	25	5-85	250	100	925	563	148	140	66	149	12
44010144B	25 STS	25	80-150	249	100	924	640	153	140	66	160	12
44010199B	30 TS	30	10-90	250	100	918	568	153	142	66	155.5	12
44010145B	30 STS	30	80-150	249	100	906	645	156	142	66	165.5	12

# Blueprint

