



## Wire Rope Clamp BG

### Product information

**General:** Wire rope clamp type, approved for lifting. Requires fewer clamps per fixation, e.g. two wire clamps instead of four, for 16 mm cable. Symmetrical – cannot be wrongly fitted. The clamps ensure fixation of the wire to a degree of at least 90% of the minimum breaking load of the wire in accordance with the current European standard.

**Design:** Bases of cast steel.

**Finish:** Body Hot dip galvanized and bolt electro galvanized

**Note:** Follow the fitting instructions in the user manual before use. Not for use with compacted or hammered wire ropes.

| Part code | Rope Ø range<br>mm | Thread | No. of clips when lifting | Torque<br>Nm | Weight<br>kg/100pc | Delivery time |
|-----------|--------------------|--------|---------------------------|--------------|--------------------|---------------|
| 47090062F | 5-6                | M6     | 2                         | 9,5          | 9                  | 12            |
| 47090063F | 6.5-8              | M6     | 2                         | 9,5          | 12                 | 12            |
| 47090064F | 8.5-10             | M8     | 2                         | 22           | 20                 | 12            |
| 47090065F | 11-12.5            | M10    | 2                         | 44           | 39                 | 12            |
| 47090066F | 13-16              | M12    | 2                         | 75           | 72                 | 2             |
| 47090067F | 17-20              | M14    | 2                         | 120          | 120                | 12            |
| 47090068F | 21-25              | M18    | 2                         | 260          | 280                | 12            |
| 47090069F | 26-34              | M20    | 2                         | 350          | 770                | 12            |