

## Ferrule T Talurit®

### Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and spiral strand ropes.

**Material:** Aluminum

**Marking:** According to standard

**Standard:** EN 13411-3

*except size range*

**Note:** See the manufacturer's product data sheet in the tab "Documents" for guidance on dimension selection.

Part Code	Ferrule size mm	Length mm	Delivery time
10.01T025	2.5	12	12
10.01T03	3	14	12
10.01T035	3.5	16	12
10.01T04	4	18	12
10.01T045	4.5	20	12
10.01T05	5	23	12

10.01T06	6	27	12
10.01T065	6.5	29	12
10.01T07	7	32	12
10.01T08	8	36	12
10.01T09	9	40	12
10.01T10	10	45	12
10.01T11	11	50	12
10.01T12	12	54	12
10.01T13	13	59	12
10.01T14	14	63	12
10.01T16	16	72	12
10.01T18	18	81	12
10.01T20	20	90	12
10.01T22	22	99	12
10.01T24	24	108	12
10.01T26	26	117	12
10.01T28	28	126	12
10.01T30	30	135	12
10.01T32	32	144	12
10.01T34	34	153	12
10.01T36	36	162	12
10.01T38	38	171	12
10.01T40	40	180	12

10.01T44	44	198	12
10.01T48	48	216	12
10.01T52	52	234	12
10.01T56	56	252	12
10.01T60	60	270	12
10.01T01	1	6.5	12
10.01T015	1.5	8	12
10.01T02	2	9	12
10.01T42	42	189	12
10.01T46	46	207	12
10.01T50	50	225	12
10.01T54	54	243	12
10.01T58	58	261	12