

## Chain SA/S - EN818-2 Gr. 10

### Product information



**General:** Chain for lifting or lashing (other safety factor). Available in 2 different qualities

**Star Alloy (SA/S):**

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

**Star Alloy Plus+ (SAP/S):** for working temperatures up to 380°C (Available on request)

**Material:** Alloy steel.

**Marking:** According to standard

**Temperature range:** Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

**Standard:** EN 818-2

*higher capacity*

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	Min. Breaking force kN	Pitch Length	D mm	P mm	Li min.	Le max.	Weight kg/m	Delivery time
42020001B	6	1.4	56.5	18	6	18	8.7	22	0.96	2
42020002B	7	1.9	77	21	7	21	9.5	25	1.2	12
42020003B	8	2.5	101	24	8	24	10.9	29	1.57	12
42020004B	10	4	157	30	10	30	13.5	36	2.46	12
42020005B	13	6.7	265	39	13	39	17.5	47	4.18	12
42020006B	16	10	402	48	16	48	21.5	58	6.28	12
42020007B	19	14	567	57	19	57	26.6	69	8.9	12
42020012B	22	19	760	66	22	66	29.5	79	11.88	12
42020011B	26	26.5	1,060	78	26	78	35	94	16.18	12

## Blueprint

