

## Chain SA/S - EN818-2 Gr. 10

### Product information



**General:** Chain for lifting or lashing (other safety factor). Available in 2 different qualities

**Star Alloy (SA/S):**

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

**Star Alloy Plus+ (SAP/S):** for working temperatures up to 380°C (Available on request)

**Material:** Alloy steel.

**Marking:** According to standard

**Temperature range:** Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

**Standard:** EN 818-2

*higher capacity*

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code | Chain diameter<br>mm | WLL<br>ton | Min. Breaking force<br>kN | Pitch Length | D<br>mm | P<br>mm | Li min. | Le max. | Weight<br>kg/m | Delivery time |
|-----------|----------------------|------------|---------------------------|--------------|---------|---------|---------|---------|----------------|---------------|
| 42020001B | 6                    | 1.4        | 56.5                      | 18           | 6       | 18      | 8.7     | 22      | 0.96           | 2             |
| 42020002B | 7                    | 1.9        | 77                        | 21           | 7       | 21      | 9.5     | 25      | 1.2            | 12            |
| 42020003B | 8                    | 2.5        | 101                       | 24           | 8       | 24      | 10.9    | 29      | 1.57           | 12            |
| 42020004B | 10                   | 4          | 157                       | 30           | 10      | 30      | 13.5    | 36      | 2.46           | 12            |
| 42020005B | 13                   | 6.7        | 265                       | 39           | 13      | 39      | 17.5    | 47      | 4.18           | 12            |
| 42020006B | 16                   | 10         | 402                       | 48           | 16      | 48      | 21.5    | 58      | 6.28           | 12            |
| 42020007B | 19                   | 14         | 567                       | 57           | 19      | 57      | 26.6    | 69      | 8.9            | 12            |
| 42020012B | 22                   | 19         | 760                       | 66           | 22      | 66      | 29.5    | 79      | 11.88          | 12            |
| 42020011B | 26                   | 26.5       | 1,060                     | 78           | 26      | 78      | 35      | 94      | 16.18          | 12            |

## Blueprint

