



Load Hook HKS/S Grade 10 - Clevis/Latch

Product information

Clevis Load hook - Sling hook with safety latch for general lifting applications.

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 380°C

Finish: Violet powder coated.

Standard: EN 1677-2

(+ 25% WLL)

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

| Part Code | Code | WLL ton | EWL mm | For chain \varnothing mm | e mm | h mm | a mm | d mm | g mm | b mm | Weight kg | Delivery time |
|-----------|-------------|---------|--------|----------------------------|------|------|------|------|------|------|-----------|---------------|
| 42050242B | HKS/S-6 | 1.4 | 69 | 6 | 69 | 20 | 15 | 7 | 19 | 66 | 0.25 | 12 |
| 42050135B | HKS/S-7 | 1.9 | 95 | 7 | 95 | 28 | 19 | 9 | 26 | 90 | 0.68 | 12 |
| 42050138B | HKS/S-8 | 2.5 | 95 | 8 | 95 | 28 | 19 | 10 | 26 | 90 | 0.58 | 12 |
| 42050128B | HKS/S-10 | 4 | 109 | 10 | 109 | 35 | 25 | 12.5 | 31 | 108 | 1.14 | 12 |
| 42050130B | HKS/S-13 | 6.7 | 136 | 13 | 136 | 41 | 34 | 16 | 39 | 131 | 2.02 | 12 |
| 42050133B | HKS/S-16 | 10 | 155 | 16 | 155 | 49 | 37 | 20 | 45 | 153 | 3.57 | 12 |
| 42050218B | HKS/S-19/20 | 16 | 184 | 19-20 | 184 | 53 | 51 | 24 | 53 | 177 | 5.55 | 2 |
| 42050534B | HKS/S-22 | 19 | 214 | 22 | 214 | 62 | 52 | 27 | 62 | 196 | 8.99 | 12 |

Blueprint

