



Load Hook HKS/S Grade 10 - Clevis/Latch

Product information

Clevis Load hook - Sling hook with safety latch for general lifting applications.

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 380°C

Finish: Violet powder coated.

Standard: EN 1677-2

(+ 25% WLL)

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	EWL mm	For chain \varnothing mm	e mm	h mm	a mm	d mm	g mm	b mm	Weight kg	Delivery time
42050242B	HKS/S-6	1.4	69	6	69	20	15	7	19	66	0.25	12
42050135B	HKS/S-7	1.9	95	7	95	28	19	9	26	90	0.68	12
42050138B	HKS/S-8	2.5	95	8	95	28	19	10	26	90	0.58	12
42050128B	HKS/S-10	4	109	10	109	35	25	12.5	31	108	1.14	12
42050130B	HKS/S-13	6.7	136	13	136	41	34	16	39	131	2.02	12
42050133B	HKS/S-16	10	155	16	155	49	37	20	45	153	3.57	12
42050218B	HKS/S-19/20	16	184	19-20	184	53	51	24	53	177	5.55	2
42050534B	HKS/S-22	19	214	22	214	62	52	27	62	196	8.99	12

Blueprint

