



## Shortening Grab Hook PK/S Grade 10 - Clevis

### Product information

Application for shortening of chain.

**Material:** Alloy steel.

**Marking:** CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code | Code       | WLL ton | EWL mm | For chain $\phi$ mm | a mm | b mm | d mm | e mm | g mm | Weight kg | Delivery time |
|-----------|------------|---------|--------|---------------------|------|------|------|------|------|-----------|---------------|
| 42050621B | PK/S-6     | 1.4     | 47     | 6                   | 26   | 42   | 7.4  | 47   | 9    | 0.2       | 12            |
| 42050622B | PK/S-7     | 1.9     | 63     | 7                   | 35   | 56   | 9    | 63   | 9    | 0.46      | 12            |
| 42050623B | PK/S-8     | 2.5     | 63     | 8                   | 35   | 56   | 10   | 63   | 9    | 0.43      | 12            |
| 42050243B | PK/S-10    | 4       | 78     | 10                  | 46   | 70   | 12.5 | 78   | 15   | 0.9       | 12            |
| 42050622B | PK/S-13    | 6.7     | 93     | 13                  | 60   | 92   | 16   | 93   | 15   | 1.71      | 12            |
| 42050748B | PK/S-16    | 10      | 115    | 16                  | 70   | 113  | 20   | 115  | 19   | 3.24      | 12            |
| 42050619B | PK/S-19-20 | 16      | 141    | 19-20               | 84   | 150  | 24   | 141  | 27   | 6.55      | 12            |
| 42050620B | PK/S-22    | 19      | 158    | 22                  | 91   | 165  | 27   | 158  | 27   | 9.28      | 12            |

## Blueprint

