



## Shortening Grab Hook P/S Grade 10 - Eye

### Product information

Eye shortening hook for shortening of chain.

**Material:** Alloy steel.

**Marking:** CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code | Code         | WLL ton | EWL mm | For chain $\varnothing$ mm | a mm | b mm | d1 mm | d2 mm | e mm | g mm | Weight kg | Delivery time |
|-----------|--------------|---------|--------|----------------------------|------|------|-------|-------|------|------|-----------|---------------|
| 42050055B | P/S-6-10     | 1.4     | 50     | 6                          | 26   | 42   | 12    | 9     | 50   | 7    | 0.15      | 12            |
| 42050056B | P/S-7/8-10   | 2.5     | 65     | 7-8                        | 35   | 42   | 16    | 12    | 65   | 9    | 0.37      | 12            |
| 42050047B | P/S-10-10    | 4       | 77     | 10                         | 46   | 70   | 20    | 14    | 77   | 12   | 0.7       | 12            |
| 42050049B | P/S-13-10    | 6.7     | 101    | 13                         | 60   | 91   | 26    | 19    | 101  | 15   | 1.52      | 12            |
| 42050051B | P/S-16-10    | 10      | 121    | 16                         | 69   | 113  | 32    | 23    | 121  | 19   | 2.9       | 12            |
| 42050052B | P/S-19/20-10 | 16      | 151    | 19-20                      | 84   | 150  | 36    | 27    | 151  | 25   | 6.15      | 12            |
| 42050617B | P/S-22-10    | 19      | 170    | 22                         | 91   | 165  | 42    | 31    | 170  | 27   | 8.3       | 12            |
| 42050533B | P/S-26-10    | 26.5    | 201    | 26                         | 107  | 195  | 50    | 37    | 201  | 32   | 13.8      | 12            |

## Blueprint

