

MULTI-STICK STRAP-GO function

User Manual

Α


Wrap the strap evenly.



The use of a strap winder ref : 48879 12 can make the process easier

В

Insert the wraped strap between the two spring




C

Put the strap on the shovel's tool being careful of the unwinding direction.



D

On the hook side, pinch the end of the strap and insert it into the slot provided for this purpose.




F

Adjust the height of the handle. Only the STRAP-GO head must exceed the height of the loads.



F

Put your hands on the handle's foam part.



Forankra

8 Rue Jacques de Vaucanson, ZA de la Pesselière 69780 MIONS info@forankra.fr - www.forankra.fr

Fax: +33 (0)4 78 21 54 71

Phone: +33 (0)4 72 45 01 20



MULTI-STICK STRAP-GO function

User Manual

G

Put yourself at +/- 50cm from the trailer.



Н

The angle between the handle and the edge of the trailer must not exceed 30°.



Ī

It is highly recommended not to touch the load with the handle during the strap launch.



J

Launch the strap above the load with a quick pulse and let it roll on the other side.




K Take back and fix the hook on the anchor point or edge.



On the other side of the semi, tension the strap using the awning tightener.



Discover the others MULTI-STICK's functions.



Ref: 49120-10

Ref: 49122-10

Forankra

8 Rue Jacques de Vaucanson, ZA de la Pesselière 69780 MIONS info@forankra.fr - www.forankra.fr

Fax: +33 (0)4 78 21 54 71

Phone: +33 (0)4 72 45 01 20