

## Kausza z stali nierdzewnej



### Informacja o produkcie



Tłoczone z profilowanej stali. Pierwszy wybór dla surowego środowiska w sektorze morskim.

**Materiał:** Nierdzewna stal kwasoodporna AISI 316.

**Zakończenie:** Polerowany

Nr artykułu	Średnica liny mm	A mm	B mm	L	S mm	Waga kg/100pcs	Przybliżony czas realizacji (dni)
10.26110002	2	3	9	16	1,0	0,2	12
10.26110003	3	4	10	17	1,0	0,3	12
10.26110004	4	5	11	19	1,35	0,5	12
10.26110005	5	6	13	21	1,2	0,7	12
10.26110006	6	7	15	27	1,5	1,1	12
10.26110007	7	8	19	33	1,5	1,4	12

10.26110008	8	9	22	38	2,0	2,6	12
10.26110009	9	10	24	43	2,0	3,1	12
10.26110010	10	11	27	46	2,7	4,9	12
10.26110012	12	14	29	52	2,7	6,6	12
10.26110014	14	16	33	57	3,0	9	12
10.26110016	16	18	40	67	3,0	11,3	12
10.26110018	18	20	45	75	4,0	19	12
10.26110020	20	22	52	84	4,0	31,2	12
10.26110022	22	24	56	93	5,0	45,5	12
10.26110026	26	28	65	112	6,0	67	12
10.26110028	28	30	80	135	5,5	82	12
10.26110032	32	34	92	160	6,25	110	12
10.26110034	34	36	105	160	6,0	117	12
10.26110036	36	38	115	176	6,0	142	12
10.26110038	38	40	120	180	8,0	206	12
10.26110040	40	42	120	192	8,0	220	12
10.26110042	42	45	150	240	8,0	304	12

Rysunek techniczny

