



Lifting Eye Nut RUD RM, UNC thread

Product information

- considerably higher WLL in comparison to DIN 582
- clear marking of the minimum WLL
- comprehensive range of threads

Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

| WLL ton | Thread Inch | A mm | B mm | C mm | D mm | E mm | T mm | Bec kg | Delivery time |
|---------|-------------|------|------|------|------|------|------|--------|---------------|
| 0,2 | 3/8 -16 | 12 | 11 | 10 | 25 | 25 | 34 | 0,1 | 12 |
| 0,35 | 1/2 -13 | 14 | 13 | 12 | 30 | 30 | 41 | 0,17 | 12 |
| 0,75 | 5/8 -11 | 16 | 15 | 14 | 35 | 35 | 48 | 0,26 | 12 |
| 1,2 | 3/4 -10 | 18 | 17 | 16 | 40 | 40 | 55 | 0,39 | 12 |
| 1,5 | 7/8 -9 | 22 | 21 | 20 | 50 | 50 | 70 | 0,7 | 12 |
| 2 | 1 -8 | 28 | 26 | 24 | 60 | 60 | 85 | 1,4 | 12 |
| 3 | 1 1/4 -7 | 28 | 26 | 24 | 60 | 60 | 85 | 1,35 | 12 |

Blueprint

