



## Lifting Eye RUD VRS-F Starpoint, UNC thread

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

**Marking:** CE-marked

**Safety factor:** 4:1

| WLL ton | Thread Inch | B mm | C mm | D mm | E mm | G mm | I mm | K mm | L mm | N mm  | T mm | Bec kg | Delivery time |
|---------|-------------|------|------|------|------|------|------|------|------|-------|------|--------|---------------|
| 0,4     | 3/8 -16     | 11   | 9    | 25   | 25   | 30   | 16,3 | 47   | 15   | 6,35  | 35   | 0,12   | 12            |
| 0,4     | 7/16 -14    | 11   | 9    | 25   | 25   | 30   | 16,3 | 47   | 15   | 6,35  | 35   | 0,12   | 12            |
| 0,75    | 1/2 -13     | 13   | 10   | 30   | 30   | 34   | 19,8 | 56   | 19   | 7,94  | 42   | 0,22   | 12            |
| 1,5     | 5/8 -11     | 15   | 13   | 35   | 36   | 40   | 23,5 | 65   | 24   | 9,53  | 49   | 0,33   | 12            |
| 2,3     | 3/4 -10     | 17   | 16   | 40   | 41   | 50   | 29,3 | 76   | 29   | 12,7  | 58   | 0,58   | 12            |
| 2,3     | 7/8 -9      | 17   | 16   | 40   | 41   | 50   | 29,3 | 76   | 33   | 12,7  | 58   | 0,61   | 12            |
| 3,2     | 1 -8        | 20   | 19   | 49   | 51   | 60   | 35   | 92   | 36   | 14,29 | 70   | 0,98   | 12            |
| 4,5     | 1 1/4 -7    | 26   | 24   | 60   | 66   | 75   | 44   | 114  | 48   | 15,88 | 87   | 2,08   | 12            |
| 7       | 1 1/2 -6    | 32   | 29   | 73   | 76   | 98   | 53   | 135  | 54   | 22,23 | 104  | 3,6    | 12            |
| 9       | 1 3/4 -5    | 37   | 33   | 84   | 86   | 111  | 62   | 158  | 63   | 25,4  | 121  | 4,95   | 12            |
| 12      | 2 -4.5      | 42   | 42   | 94   | 100  | 128  | 70   | 180  | 72   | 28,58 | 138  | 7,6    | 12            |

# Blueprint

