



## Lifting Eye RUD VWBG

### Product information

- Rotates 360°, pivots 230°
- Indicator markings to highlight wear and damage to load ring
- Ball bearing

According to the Machinery Directive 2006/42/EC

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

| Код товара   | WLL   | A<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | M<br>mm | T<br>mm | Bec   | Delivery time |
|--------------|-------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-------|---------------|
| -            | 8     | 22      | 86      | 50      | 90      | 80      | 54      | 94      | M36     | 208     | 4,72  | 12            |
| -            | 12    | 26      | 111     | 65      | 98      | 85      | 63      | 95      | M42     | 234     | 6,1   | 12            |
| -            | 12    | 26      | 11      | 65      | 98      | 85      | 67      | 95      | M45     | 234     | 6,24  | 12            |
| -            | 13    | 26      | 111     | 65      | 98      | 85      | 68      | 95      | M48     | 234     | 6,37  | 12            |
| -            | 14    | 32      | 119     | 70      | 120     | 95      | 78      | 120     | M52     | 271     | 10,55 | 12            |
| -            | 16    | 32      | 119     | 70      | 120     | 95      | 94      | 120     | M64     | 271     | 11,4  | 12            |
| 11.427999004 | 23,55 | 32      | 119     | 70      | 120     | 95      | 84      | 120     | M56     | 271     | 10,68 | 12            |
| -            | 31,5  | 46      | 130     | 90      | 170     | 145     | 108     | 159     | M72     | 338     | 29,96 | 12            |

## Blueprint

