



## Lifting Eye Starpoint RUD VRS

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly available, look type VRS-F

**Safety factor:** 4:1

| Код товара | WLL ton | B mm | C mm | D mm | E mm | G mm | I mm | K mm | L mm | M mm | N mm | T mm | Bec kg | Delivery time |
|------------|---------|------|------|------|------|------|------|------|------|------|------|------|--------|---------------|
| 42040255B  | 0,3     | 11   | 9    | 25   | 25   | 30   | 16,3 | 47   | 12   | M8   | 6    | 35   | 0,11   | 12            |
| -          | 0,4     | 11   | 9    | 25   | 25   | 30   | 16,3 | 47   | 15   | M10  | 6    | 35   | 0,11   | 12            |
| 42040254B  | 0,75    | 13   | 10   | 30   | 30   | 34   | 19,8 | 56   | 18   | M12  | 8    | 42   | 0,19   | 12            |
| -          | 0,75    | 13   | 10   | 30   | 30   | 30   | 34   | 19,8 | 56   | 18   | M14  | 8    | 0,2    | 12            |
| -          | 1,5     | 15   | 13   | 35   | 36   | 40   | 23,5 | 65   | 24   | M16  | 10   | 49   | 0,32   | 12            |
| -          | 2,3     | 17   | 16   | 40   | 41   | 50   | 29,3 | 76   | 30   | M20  | 12   | 58   | 0,54   | 12            |
| -          | 3,2     | 20   | 19   | 49   | 51   | 60   | 35   | 92   | 36   | M24  | 14   | 70   | 0,86   | 12            |
| -          | 4,5     | 26   | 24   | 60   | 66   | 75   | 44   | 114  | 45   | M30  | 17   | 87   | 1,5    | 12            |
| -          | 7       | 32   | 29   | 73   | 76   | 98   | 53   | 135  | 54   | M36  | 22   | 104  | 3,3    | 12            |

## Blueprint

