



Lifting Eye Starpoint RUD VRS-F

Product information

Star shaped design, can be adjusted to the direction of pull. Higher load capacities than DIN 580-Eyebolts

Marking: According to standard

Standard: EN 1677-1

Safety factor: 4:1

Код товара	Код	WLL ton	Thread mm	Thread	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Вес kg	Delivery time
46040185B	VRS-F	0,1	M6	M6	15	13	35	36	40	23,5	65	24	10	49	0,07	12
46040186B	VRS-F	0,3	M8	M8	11	9	25	25	30	16,3	47	12	6	35	0,12	12
46040187B	VRS-F	0,4	M10	M10	11	9	25	25	30	16,3	47	15	6	35	0,12	12
46040159B	VRS-F	0,75	M12	M12	13	10	30	30	34	19,8	56	18	8	42	0,21	12
46040188B	VRS-F	0,75	M14	M14	13	10	30	30	34	19,8	56	18	8	42	0,22	12
46040189B	VRS-F	1,5	M18	M18	15	13	35	36	40	23,5	65	24	10	49	0,39	12
46040119B	VRS-F	2,3	M20	M20	17	16	40	41	50	-	76	30	12	58	0,6	12
46040191B	VRS-F	3,2	M24	M24	20	19	49	51	60	35	92	36	14	70	1,05	12
46040192B	VRS-F	3,2	M27	M27	20	19	49	51	60	35	92	36	M27	70	1,18	12
46040193B	VRS-F	4,5	M30	M30	26	24	60	66	75	44	114	45	17	87	2,08	12
46040195B	VRS-F	7	M36	M36	32	29	73	76	98	53	135	54	22	104	3,49	12
46040196B	VRS-F	9	M42	M42	37	33	84	86	111	62	158	63	24	121	5,4	12
46040197B	VRS-F	12	M48	M48	42	42	94	100	128	70	180	72	27	138	8,17	12

Blueprint

