

Electric E-winch 250-3000kg

Product information



Electric winch for pulling and lifting with a powerful three-phase motor. It's budget-friendly and strong in its work.

- winch suitable for lifting (with included limit switch)
- maintenance free bearings
- protection classification IP54, insulation class F
- standard overload protection as from 1000 kg
- powerfull three-phase motor for multirange voltage:
230 – 400V / 50 Hz - three phase
480V / 60 Hz (torque -20%, speed +20%)
- 1 speed pendant control with 1m cable
- standard 2 meter power cable including 16A CEEplug
- 1 layer of paint

Options:

- for pulling applications (without included limit switch)
- pressure roller (PR)
- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- external limit switch (EL)
- protection classification IP55 (IP55)

Marking: CE-marked

Код товара	WLL ton	Lifting speed m/min	Motor kW	Rope capacity m	Capacity top layer kg	Rope diameter mm	A1	A2	A3	A4	A5	A6	A7	A8	B	B1	C	C1	C2	D	D1	Bec kg	Delivery time
5406e-W250	0,25	5,2	0,37	122	109	4	269	151	222	47	59	146	64	17	550	440	355	190	6	55	150	52	12
5406e-W500	0,5	5,4	0,75	45	247	6	269	189	222	47	59	146	64	17	550	440	355	190	6	55	150	60	12
5406e-W1000	1	3,5	1,1	100	570	8	475	172	405	70	130	265	80	27	610	500	455	255	8	102	220	107	12
5406e-W1500	1,5	4,4	1,8	55	927	10	475	211	405	70	130	265	80	27	610	500	455	255	8	102	220	122	12
5406e-W2000	2	4,7	2	94	998	12	475	220	405	70	149	241	85	27	700	570	515	260	8	168	325	180	12
5406e-W3000	3	3,6	3	54	1 957	14	475	240	405	70	149	241	85	27	700	570	515	260	8	168	325	192	12

Blueprint

