



## Heavy Duty Air Chain Hoists Red Rooster TMH (37.500 & 45.000 kg)

### Product information

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market.

#### Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

#### ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

#### Recommended:

We highly recommend the use of an SMC air treatment unit. (Sold separately).

**Marking:** According to standard, CE-marked

**Standard:** EN 14492-2

WLL ton	Type	Chain falls	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Lifting speed with max.load m/min	Lowering speed with max.load m/min	Lifting speed without load m/min	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	M mm	N mm	O mm	P mm	Q mm	Bec kg	Delivery time
37,5	Cord control	3	180	108	0,9	2	1,8	1440	1505	57,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1300	12
37,5	Pendant control	3	180	108	0,9	2	1,8	1440	1505	57,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1300	12
45	Cord control	3	167	108	0,65	1,8	1,8	1440	1505	57,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1300	12
45	Pendant control	3	167	108	0,65	1,8	1,8	1440	1505	57,5	592,5	118	90	830	380	675	125	118	545	352	256	112	112	300	1300	12

## Blueprint

