



## Geared trolley

### Product information

Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157

**Safety factor:** 4:1

| Код товара | WLL ton | Beam width mm | Min. Radius Curve m | A mm  | B mm | C mm  | D mm | E mm | F mm | G mm | H mm | Bec kg | Delivery time |
|------------|---------|---------------|---------------------|-------|------|-------|------|------|------|------|------|--------|---------------|
| 43030016F  | 1       | 58-220        | 0,7                 | 353,5 | 238  | 183   | 17   | 31   | ~3   | 68   | 95   | 12,5   | 2             |
| 43030017F  | 2       | 66-220        | 0,9                 | 362   | 277  | 208   | 20   | 31   | ~3   | 80   | 108  | 17     | 2             |
| 43030018F  | 3       | 74-220        | 1,2                 | 406,5 | 324  | 249   | 26   | 31   | ~3   | 100  | 131  | 28     | 2             |
| 43030019F  | 5       | 90-220        | 1                   | 434,5 | 373  | 296,5 | 28   | 40   | ~5   | 120  | 154  | 45     | 2             |
| 43030013F  | 10      | 125-203       | 1,3                 | 487,5 | 455  | 490   | 82   | 36,5 | ~5   | -    | -    | 93     | 2             |
| SIVA200HKS | 20      | 136-203       | 4,7                 | 523   | 642  | 622   | 110  | 54   | ~5   | -    | -    | 247,5  | 12            |

# Blueprint

