



Push trolley

Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

Код товара	WLL ton	Beam width mm	Minimum radius mm	B mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Bec kg	Delivery time
43030001F	0,5	55-220	500	285	3	40	12,5	25	80	198	158	55	5	2
43030002F	1	58-220	700	300	3	31	17	29	96	238	183	68	8,8	2
43030009F	1	58-305	700	238	3	31	17	29	96	-	183	68	9,3	12
43030003F	2	66-220	900	300	3	31	20	36	110	277	208	80	14	2
43030021F	2	66-305	900	405	3	31	20	36	110	277	208	80	14,8	12
43030004F	3	74-220	1 200	328	3	31	26	46	132	324	249	100	23	2
43030022F	3	74-305	1 200	429	~3	31	26	46	132	324	249	100	24,1	2
43030005F	5	90-220	1 000	354	5	40	28	52	155	373	296,5	120	40	2
43030012F	5	90-305	1 000	435	~5	40	28	52	155	373	296,5	120	41,1	12

Blueprint

