



## Push trolley

### Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

**Marking:** According to standard, CE-marked

**Standard:** EN 13157

**Safety factor:** 4:1

Код товара	WLL ton	Beam width mm	Min. Radius Curve m	B mm	J mm	K mm	F mm	E mm	D mm	L mm	H mm	G mm	Bec kg	Delivery time
43030001F	0,5	55-220	0,5	285	198	158	12,5	40	3	55	80	25	5	2
43030002F	1	58-220	0,7	300	238	183	17	31	3	68	96	29	8,8	2
43030009F	1	58-305	0,7	238	-	183	17	31	3	68	96	29	9,3	12
43030003F	2	66-220	0,9	300	277	208	20	31	3	80	110	36	14	2
43030021F	2	66-305	0,9	405	277	208	20	31	3	80	110	36	14,8	12
43030004F	3	74-220	1,2	328	324	249	26	31	3	100	132	46	23	12
43030022F	3	74-305	1,2	429	324	249	26	31	~3	100	132	46	24,1	2
43030005F	5	90-220	1	354	373	296,5	28	40	5	120	155	52	40	2
43030012F	5	90-305	1	435	373	296,5	28	40	~5	120	155	52	41,1	12

## Blueprint

