



## Lifting eye screw DIN 580

### Product information

Lifting eye screws for vertical lifting

**Marking:** According to standard, CE-marked

**Standard:** DIN 580

**Safety factor:** 4:1

Код товара	WLL ton	Thread d1	Packing	Thread pitch mm	d2 mm	d3 mm	d4 mm	h mm	k mm	l mm	Bec kg	Delivery time
46040030F	0,08	M 6	50	1	20	36	20	18	8	13	0,045	12
46040031F	0,14	M 8	50	1,25	20	36	20	18	8	13	0,05	12
46040019F	0,23	M10	50	1,5	25	45	25	22,5	10	17	0,09	2
46040020F	0,34	M12	25	1,75	30	54	30	26	12	20,5	0,16	2
46040032F	0,34	M14	25	2	35	63	35	30,5	14	27	0,24	2
46040021F	0,7	M16	10	2	35	63	35	30,5	14	27	0,24	12
46040022F	1,2	M20	10	2,5	40	72	40	35	16	30	0,36	12
46040023F	1,8	M24	1	3	50	90	50	45	20	36	0,72	12
46040041F	3,2	M33	1	3,5	65	108	60	55	24	45	1,3	12
46040024F	3,2	M30	1	3,5	65	108	60	55	24	45	1,32	2
46040043F	4,6	M39	1	4	75	126	70	65	28	54	2,02	12
46040042F	4,6	M36	1	4	75	126	70	65	28	54	2,08	12
46040045F	6,3	M45	1	4,5	85	144	80	75	32	63	3,04	12
46040044F	6,3	M42	1	4,5	85	144	80	75	32	63	3,11	12
46040047F	8,6	M52	1	5	100	166	90	85	38	68	4,95	12
46040046F	8,6	M48	1	5	100	166	90	85	38	68	5,02	12
46040048F	11,5	M56	1	5,5	110	184	100	95	42	78	6,69	12
46040049F	16	M64	1	6	120	206	110	105	48	90	9,3	12

# Blueprint

