



Lifting eye Screw

Product information

Lifting for all lifting directions.

WLL for vertical lifting is marked on the eye.

The depth of the threaded hole has to be minimum:

d = diameter of the lifting eye thread

- 1*d for steel
- 1,25*d for cast iron
- 2*d for aluminum alloys
- 2,5*d for aluminum magnesium alloys

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

| Код товара | WLL ton | Size | Dia Eye mm | Thread pitch mm | D mm | L mm | K mm | Bec kg | Delivery time |
|------------|---------|------|------------|-----------------|------|------|------|--------|---------------|
| 46010013F | 0,4 | M6 | 16 | 1 | 28 | 42 | 13 | 0,05 | 12 |
| 46010014F | 0,8 | M8 | 20 | 1,25 | 39 | 51 | 15 | 0,06 | 2 |
| 46010015F | 1 | M10 | 25 | 1,5 | 45 | 63 | 18 | 0,11 | 2 |
| 46010016F | 2 | M12 | 30 | 1,75 | 54 | 75 | 22 | 0,18 | 12 |
| 46010017F | 3 | M14 | 35 | 2 | 63 | 88 | 28 | 0,28 | 2 |
| 46010018F | 4 | M16 | 35 | 2 | 63 | 88 | 28 | 0,28 | 2 |
| 46010019F | 6 | M20 | 40 | 2,5 | 72 | 101 | 30 | 0,45 | 2 |
| 46010020F | 8 | M24 | 50 | 3 | 90 | 128 | 38 | 0,87 | 2 |
| 46010021F | 12 | M30 | 60 | 3,5 | 108 | 154 | 45 | 1,66 | 12 |
| 46010022F | 16 | M36 | 70 | 4 | 126 | 183 | 55 | 2,65 | 2 |
| 46010023F | 24 | M42 | 80 | 4,5 | 144 | 212 | 65 | 4,03 | 2 |
| 46010024F | 32 | M48 | 90 | 5 | 166 | 238 | 70 | 6,38 | 12 |

Blueprint

