



## Lifting eye screw with swivel, grade 80

### Product information

Lifting screw with swivel for all lifting directions. Also available with longer 120 mm thread.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

Код товара	WLL ton	Thread mm	Thread length mm	diameter eye inside mm	Ø of eye mm	Thread pitch mm	b mm	g mm	t mm	Bec kg	Delivery time
46030006F	0,45	M10	18	55x30	14	1,5	36	51	41	0,43	2
46030007F	0,5	M12	18	55x30	14	1,75	36	51	41	0,44	2
46030008F	1,1	M16	20	55x30	14	2	36	52	42	0,46	2
46030009F	1,1	M16	120	55x30	14	2	36	52	42	0,46	2
46030010F	2	M20	30	70x34	16	2,5	50	68	56	0,96	2
46030019F	2	M20	120	70x34	16	2,5	50	68	56	0,96	12
46030020F	3,2	M24	120	85x37	18	3	57	78	65,5	1,45	2
46030012F	3,2	M24	40	85x37	18	3	57	78	65,5	1,45	2
46030023F	5,3	M30	120	85x37	20	3,5	66	97	80,5	2,17	2
46030013F	5,3	M30	35	85x37	20	3,5	66	97	80,5	2,17	12
46030014F	8	M30	35	115x50	22	3,5	80	112	92	3,57	2
46030024F	8	M30	120	115x50	22	3,5	80	112	92	3,57	2
46030015F	8	M36	50	115x50	22	4	80	109	89,5	4,17	2
46030026F	8	M36	120	115x50	22	4	80	109	89,5	4,17	2
46030027F	10	M42	50	115x50	25	4,5	80	109	89,5	3,67	2
46030016F	10	M48	50	115x50	25	5	80	109	89,5	4,02	12
46030028F	10	M45	60	115x50	25	4,5	80	109	89,5	4,17	2
46030017F	15	M56	84	152x70	32	5,5	117	310	280	11,6	2

# Blueprint

