

## Electro galvanized shackles DIN 82101

### Product information

Electro galvanized shackles approved for lifting.

**Marking:** CE-marked

**Safety factor:** 5:1



Код товара	WLL ton	Packing	d4 mm	b1 mm	d1 mm	d2 mm	h1 mm	Bec kg	Delivery time
46080008F	0,1	50	5	7	4	5	15	0,017	12
46080005F	0,16	50	6	8	5	6	18	0,024	12
46080010F	0,25	50	8	11	7	8	24	0,054	2
46080001F	0,4	25	10	14	8	10	30	0,097	2
46080002F	0,6	25	12	17	10	12	36	0,18	12
46080009F	1	25	16	21	13	15	49	0,3	12
46080011F	1,6	25	20	27	17	19	61	0,57	12
46080012F	2	1	22	30	19	21	67	0,98	12
46080014F	2,5	1	24	33	21	23	73	1,3	12
46080004F	3	1	27	38	24	26	84	1,85	2
46080015F	4	1	30	42	27	29	91	2,53	12
46080016F	5	1	36	47	30	33	111	4	12
46080018F	8	1	45	60	38	41	140	7,9	12
46080003F	10	1	48	66	42	45	147	10	12
46080006F	16	1	60	81	52	55	185	19,2	12
46080013F	20	1	68	90	58	60	211	28	12

# Blueprint

