



## Snatch Block 0,5 - 5,0 t

### Product information

Intended for general lifting purposes. Can also be used for pulling. Side opening snatch block for wire rope with hook ends. Equipped with slide bearings, with grease nipple or aperture.

**Marking:** CE-marked

| <b>Код товара</b> | <b>Rope Ø range<br/>mm</b> | <b>WLL<br/>ton</b> | <b>Height<br/>mm</b> | <b>Wheel size<br/>mm</b> | <b>Bec<br/>kg</b> | <b>Delivery time</b> |
|-------------------|----------------------------|--------------------|----------------------|--------------------------|-------------------|----------------------|
| 46100015F         | 8                          | 0,5                | 269                  | 75                       | 1,6               | 2                    |
| 46100001F         | 10                         | 1                  | 316                  | 100                      | 3,5               | 2                    |
| 46100002F         | 13                         | 1,5                | 370                  | 125                      | 4,6               | 2                    |
| 46100003F         | 16                         | 2                  | 445                  | 150                      | 7,7               | 2                    |
| 46100005F         | 19                         | 3                  | 496                  | 180                      | 11                | 2                    |
| 46100007F         | 22                         | 4                  | 589                  | 200                      | 19,3              | 2                    |
| 46100028F         | 25                         | 5                  | 705                  | 250                      | 33,8              | 12                   |