



Stainless steel shackles, approved for lifting

Product information

Stainless steel shackles approved for lifting.

Marking: CE-marked

Safety factor: 5:1

| Код товара | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | Вес kg | Delivery time |
|------------|---------|------|------|------|------|------|------|--------|---------------|
| 46050006F | 0,4 | 8 | 8 | 16 | 16 | 32 | 52 | 0,06 | 12 |
| 46050007F | 0,6 | 10 | 10 | 19 | 20 | 40 | 64 | 0,12 | 12 |
| 46050008F | 0,9 | 12 | 12 | 24 | 25 | 48 | 78 | 0,21 | 12 |
| 46050009F | 1,5 | 13 | 16 | 31 | 24 | 52 | 90 | 0,34 | 12 |
| 46050010F | 2,5 | 16 | 20 | 38 | 28 | 64 | 110 | 0,61 | 12 |
| 46050011F | 3 | 19 | 22 | 44 | 32 | 72 | 124 | 0,9 | 12 |
| 46050012F | 4 | 22 | 25 | 50 | 37 | 74 | 134 | 1,08 | 12 |
| 46050013F | 6 | 25 | 30 | 57 | 40 | 94 | 162 | 2,25 | 12 |

Blueprint

