



Eye self-locking hook with swivel, grade 80

Product information

Due to the swivel the hook is easy to align into the wanted direction. The hook locks automatically when lifting starts.

Marking: According to standard, CE-marked

Standard: EN 1677-3

Safety factor: 4:1

Класс: 8

| Код товара | WLL ton | EWL mm | For chain dia. mm | K mm | E mm | B mm | F mm | R mm | A mm | Bec kg | Delivery time |
|------------|------------|-----------|----------------------|---------|---------|---------|---------|---------|---------|-----------|---------------|
| 42040301F | 1,12 | 160 | 6 | 170 | 29 | 22 | 11 | 34 | 32 | 0,71 | 12 |
| 42040259F | 2 | 200 | 7/8 | 210 | 34 | 26 | 12 | 46 | 35 | 1,1 | 2 |
| 42040256F | 3,15 | 230 | 10 | 247 | 44 | 34 | 15 | 56 | 42 | 2 | 2 |
| 42040257F | 5,3 | 280 | 13 | 302 | 52 | 38 | 16 | 69 | 50 | 4 | 12 |
| 42040258F | 8 | 360 | 16 | 383 | 60 | 55 | 21 | 86 | 61 | 7,3 | 2 |
| 42040334F | 12,5 | 390 | 20 | 418 | 83 | 61 | 26 | 100 | 72 | 11,6 | 2 |

Blueprint

