



## Eye sling hook with latch, grade 80

### Product information

Hook is equipped with spring loaded safety latch.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-2

**Safety factor:** 4:1

**Класс:** 8

| Код товара | WLL<br>ton | EWL<br>mm | For chain dia.<br>mm | K<br>mm | E<br>mm | F<br>mm | R<br>mm | A<br>mm | Bec<br>kg | Delivery time |
|------------|------------|-----------|----------------------|---------|---------|---------|---------|---------|-----------|---------------|
| 42040152F  | 1,12       | 76        | 6                    | 108     | 24      | 9       | 21      | 20      | 0,3       | 2             |
| 42040155F  | 2          | 90        | 7/8                  | 133     | 30      | 11      | 26      | 25      | 0,4       | 2             |
| 42040142F  | 3,15       | 117       | 10                   | 167     | 34      | 15      | 39      | 38      | 0,9       | 2             |
| 42040144F  | 5,3        | 152       | 13                   | 213     | 39      | 19      | 54      | 43      | 1,7       | 2             |
| 42040146F  | 8          | 178       | 16                   | 255     | 46      | 23      | 64      | 50      | 3,2       | 2             |
| 42040148F  | 12,5       | 226       | 20                   | 305     | 40      | 24      | 80      | 62      | 5,8       | 2             |
| 42040149F  | 15         | 249       | 22                   | 348     | 71      | 32      | 80      | 62      | 8,5       | 2             |
| 42040150F  | 21,2       | 284       | 26                   | 394     | 81      | 35      | 82      | 64      | 13        | 2             |
| 42040151F  | 31,5       | 346       | 32                   | 480     | 102     | 37      | 112     | 68      | 17        | 2             |

## Blueprint

