

Lifting chain, grade 80

Product information

Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

Marking: According to standard

Standard: EN 818-2

Safety factor: 4:1

Класс: 8



| Код товара | Chain diameter mm | WLL ton | A mm | B mm | D mm | Вес kg/m | Delivery time |
|------------|----------------------|------------|---------|---------|---------|-------------|---------------|
| 42010001F | 6 | 1,12 | 18 | 9 | 6 | 0,8 | 2 |
| 42010016F | 7 | 1,5 | 22 | 10 | 7 | 1,1 | 12 |
| 42010002F | 8 | 2 | 24 | 12 | 8 | 1,35 | 2 |
| 42010004F | 10 | 3,15 | 30 | 14 | 10 | 2,15 | 2 |
| 42010005F | 13 | 5,3 | 39 | 19 | 13 | 3,5 | 2 |
| 42010006F | 16 | 8 | 48 | 23 | 16 | 5,5 | 2 |
| 42010007F | 20 | 12,5 | 60 | 25 | 20 | 8,4 | 12 |
| 42010008F | 22 | 15 | 66 | 28 | 22 | 10,35 | 2 |
| 42010009F | 26 | 21,2 | 78 | 35 | 26 | 15,8 | 12 |
| 42010010F | 32 | 31,5 | 96 | 43 | 32 | 23 | 2 |

Blueprint

