

Low Speed Electric Winch LS5000

Інформація про товар



Low-speed electric winch, made to move fragile loads from 0,3 metres per minute, powerful with its 5 ton lifting capacity in combination with a 230V connection.

- robust and safe electric pulling and lifting winch 400 V / 230 V
- protection classification electric IP55 / mechanical IP54
- mechanical overload protection
- thermal protection electric motor
- low voltage (24 V) pendant switch with 2 m cable
- including 2 m power cable with 16A CEE plug
- automatic grease system for the worm gearing
- 1 layer of paint

Options:

- limit switch - required for lifting applications (LS)
- grooved drum (GD)
- 230V - 50Hz

Маркування: Згідно зі стандартом, CE-marked

Стандарт: EN 14492

| Вантажопідйомність тон | Швидкість підйому м/хв | Motor kW | Capacity top layer kg | Діаметр троса мм | A | B | C | D | E | F | G | H | J | K | L | M | N | P | R | Bara | Delivery time |
|---------------------------|------------------------|-------------|--------------------------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|------|---------------|
| | | | | | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg | |
| 5 | 0,4 | 0,75 | 3 959 | 18 | 730 | 704 | 630 | 600 | 169 | 534 | 183 | 322 | 219 | 25 | 351 | 126 | 254 | 427 | 255 | 216 | 12 |

Креслення

